

REMOTE AIR COOLED CONDENSER - SCREW – 134A														
Model	THR (Btu/Hr)	AIR COOLED CONDENSER { T <sub>amb</sub> = 95 F T <sub>cond</sub> = 120 F }												
		Use for Chiller Model	Refriger. Circuits	Fans 1140 RPM Motors, 1 ½ HP			Connection Size OD (inch)		Refrigerant Charge (lbs)		Dimensions (inch)			Shipping Weight (lbs)
				Wide/Long	Row	Fins/Inch	Inlet	Outlet	Summer	Winter	L	W	H	
SINGLE SCREW COMPRESSOR - CONDENSERLESS AIR COOLED CHILLERS														
TRAC-060SSY	719,000	WCL060SSY	1	1 X 4	3	1 2	2 1/8	1 5/8	26	105	219	52	49	1,550
TRAC-070SSY	806,000	WCL070SSY	1	1 X 4	4	1 2	2 1/8	2 1/8	34	140	219	52	49	1,680
TRAC-080SSY	1,009,000	WCL080SSY	1	1 X 5	4	1 2	2 1/8	2 1/8	43	174	273	52	53	2,335
TRAC-090SSY	1,145,000	WCL090SSY	1	1 X 6	4	0 9	2 1/8	1 5/8	95	389	327	52	53	2,925
TRAC-100SSY	1,341,000	WCL100SSY	1	2 X 4	3	1 2	(2) 2 1/8	(2) 1 5/8	52	209	219	97	49	2,835
TRAC-120SSY	1,505,000	WCL120SSY	1	2 X 4	4	0 9	(2) 2 1/8	(2) 1 5/8	69	279	219	97	49	2,990
TRAC-140SSY	1,715,000	WCL140SSY	1	2 X 4	4	1 2	(2) 2 1/8	(2) 1 5/8	69	279	219	97	49	3,100

ALL MODELS COME WITH FAN CYCLING FROM THE 2nd FAN ON.

OPTIONS AVAILABLE:

- 1 – COPPER FINES
- 2 – COATED FINES
- 3 – FAN SPEED CONTROL OF FIRST FAN
- 4 – 830 RPM LOW NOISE FANS