

REMOTE AIR COOLED CONDENSER - SCROLL – 134A														
Model	THR (Btu/Hr)	AIR COOLED CONDENSER { T _{amb} = 95 F T _{cond} = 120 F }												
		Use for Chiller Model	Refriger. Circuits	Fans 1140 RPM Motors, 1 ½ HP			Connection Size OD (inch)		Refrigerant Charge (lbs)		Dimensions (inch)			Shipping Weight (lbs)
				Wide/Long	Row	Fins/Inch	Inlet	Outlet	Summer	Winter	L	W	H	
DUAL SCROLL COMPRESSOR - CONDENSERLESS AIR COOLED CHILLERS														
TRAC-15DZY	155,000	WCL015DZY	2	1 X 1	3	0 9	1 3/8	1 1/8	7	28	57	52	49	490
TRAC-20DZY	207,000	WCL020DZY	2	1 X 1	4	1 2	1 3/8	1 1/8	9	37	57	52	49	535
TRAC-25DZY	256,000	WCL025DZY	2	1 X 2	2	1 2	1 5/8	1 3/8	9	38	111	52	49	765
TRAC-30DZY	308,000	WCL030DZY	2	1 X 2	3	0 9	1 5/8	1 3/8	13	53	111	52	49	815
TRAC-40DZY	400,000	WCL040DZY	2	1 X 2	4	1 2	1 5/8	1 3/8	17	71	111	52	49	900
TRAC-50DZY	467,000	WCL050DZY	2	2 X 2	2	0 9	(2) 1 5/8	(2) 1 3/8	18	71	111	97	49	1,375
TRAC-70DZY	806,000	WCL070DZY	2	2 X 2	4	1 2	(2) 1 5/8	(2) 1 3/8	34	142	111	97	49	1,665

ALL MODELS COME WITH FAN CYCLING FROM THE 2nd FAN ON.

OPTIONS AVAILABLE:

- 1 – COPPERS FINES
- 2 – COATED FINES
- 3 – FAN SPEED CONTROL OF FIRST FAN
- 4 – 830 RPM LOW NOISE FANS

