



NOTES:

1. **CASING:** HEAVY DUTY FRAME AND PANELS FROM SATIN COATED SHEET METAL WITH A BAKED ON POWDER PAINT.
2. **CONDENSER COIL:** HIGH PERFORMANCE BRAZED ALUMINUM CONDENSER COIL. VERTICAL MICRO-CHANNEL TUBES.
3. **FAN:** INSTALLED ON 1 HP 850 RPM MOTOR WITH INTERNAL OVERLOAD PROTECTION. 30" DIA. FANS BLADES WITH A STEEL SPUN VENTURI TO PROVIDE MAXIMUM FAN EFFICIENCY AND MINIMUM NOISE.
4. **COMPRESSOR:** SUCTION GAS COOLED DUAL SCROLL COMPRESSORS WITH OIL SIGHT GLASS, EXTERNAL "BAND TYPE" CRANKCASE HEATER.
5. **EVAPORATOR:** DESIGN WATER FLOW 2.4 GPM/TON.
6. **WATER PIPING:** SCH. 40 STEEL HEADERS AND BRANCH PIPES WITH ISOLATION VALVES.
7. **REFRIGERATION PIPING:** ACR TYPE L SEAMLESS COPPER TUBING.
8. **CONTROLS:** COMPRESSOR CONTACTORS, FANS WITH PRESSURE CYCLING, CONTROL TRANSFORMER 24/1/60, HIGH AND LOW PRESSURE SENSORS, MANUAL RESET HIGH PRESSURE SAFETY SWITCH, EVAPORATOR WATER FLOW SWITCH, ENTERING AND LEAVING WATER TEMPERATURE SENSORS, NEMA 4 CONTROL PANEL, COMPRESSOR, FAN AND TRANSFORMER FUSES.

CHILLER WEIGHT (SHIP)	WATER HEADERS	VOLT	COMPRESSOR (C)				CONDENSER FAN				MCA	MOP	RFS
			QTY	HP	RLA	LRA	QTY	HP	RPM	FLA			
1,250 LBS	ø4"~ø6"	575	2	5	7.4	50	1	1	850	2.1	20	30	20
		460			9.0	62				2.6	24	35	25
		230			18.3	123				5.3	48	70	60
		208			18.3	123				5.3	48	70	60

RLA: RATED LOAD AMPS
 LRA: LOCKED ROTOR AMPS
 MCA: MIN. CIRCUIT AMPACITY
 MOP: MAX. OVERLOAD PROTECTION
 RFS: RECOMMENDED FUSE SIZE

TANDEM CHILLERS



TANDEM CHILLERS

MODEL NO.		VX010DZV									
TITLE							V-COIL AC CHILLER & 30" FAN R410A				
SCALE	PROVED	DRAWN	DATE	JOB NO.	DRAWING NO.	REV.					
3/8"=1'-0"	R.L.	I.C.	JAN.31, 14	---	31-0308	1st					